



PCT/GB 2004 / 0 0 1 2 9 7



INVESTOR IN PEOPLE

## PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales

REC'D 27 APR 2004  
NP10 8QQ WPO PCT


I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

I also certify that the application is now proceeding in the name as identified herein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed *He Behen*  
Dated 15 April 2004

### BEST AVAILABLE COPY



INVESTOR IN PEOPLE

GB 0307558.7

By virtue of a direction given under Section 30 of the Patents Act 1977, the application is proceeding in the name of

QUINTEL TECHNOLOGY LIMITED,  
18 Upper Grosvenor Street,  
LONDON,  
W1K 7PW,  
United Kingdom

Incorporated in the United Kingdom,

[ADP No. 08697401001]

- 2 APR 2003

The  
Patent  
Office

02APR03 ET96968-1 D02776/  
POL/7700 0.00-0307558.7

NEWPORT

# Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road  
Newport  
Gwent NP9 1RH

1. Your reference

IP/P7240

2. Patent application number

(The Patent Office will fill in this part)

02 APR 2003

0307558.7

3. Full name, address and postcode of the or of each applicant (underline all surnames)

QINETIQ LIMITED

Registered Office 85 Buckingham Gate  
London SW1E 6PD  
United Kingdom

08587376002

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

SECTION 30 (1977 ACT) APPLICATION FILED 11/8/03

4. Title of the invention

Phased Array Antenna System with Variable Electrical Tilt

5. Name of your agent (if you have one)

Arthur Wyn Spencer Williams

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

QINETIQ LIMITED  
IP Formalities  
A4 Bldg  
Cody Technology Park  
Ively Road  
Farnborough  
Hants GU14 0LX United Kingdom

Patents ADP number (if you know it)

08183873005

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number  
(if you know it)

Date of filing  
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number or earlier application

Date of filing  
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body. See note (d))

YES (b)

Enter the number of sheets for any of the following items you are filing with this form.  
Do not count copies of the same document

Continuation sheets of this form

Description 23 /

Claim(s) 4 /

Abstract 1 /

Drawing(s) 11 - 11 /

10. If you are also filing any of the following, state how many against each item.

Priority documents 0

Translations of priority documents 0

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*) 2 /

Request for preliminary examination and search (*Patents Form 9/77*) 1 /

Request for substantive examination (*Patents Form 10/77*) 0

Any other documents 0  
(please specify)

11. I / We request the grant of a patent on the basis of this application.

Signature

*AWS Williams*

AWS Williams

Date 1 April 2003

12. Name and daytime telephone number of person to contact in the United Kingdom

Mrs Linda Bruckshaw 01252 392722

**Warning**

*After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent of the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.*

**Notes**

- If you need help to fill in this form or have any questions, please contact the Patent Office on 0645 500505.*
- Write your answers in capital letters using black ink or you may type them.*
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- If you have attached 'Yes' Patents Form 7/77 will need to be filed.*
- Once you have filled in the form you must remember to sign and date it.*
- For details of the fee and ways to pay please contact the Patent Office.*

The present invention relates to a phased array antenna system with variable electrical tilt. The antenna system is suitable for use in many telecommunications systems, but finds particular application in cellular mobile radio networks, commonly referred to as mobile telephone networks. More specifically, but without limitation, the antenna system of the invention may be used with second generation (2G) mobile telephone networks such as the GSM system, and third generation (3G) mobile telephone networks such as the Universal Mobile Telephone System (UMTS).

10 Operators of cellular mobile radio networks generally employ their own base-stations, each of which has at least one antenna. In a cellular mobile radio network, the antennas are a primary factor in defining a coverage area in which communication to the base station can take place. The coverage area is generally divided into a number of overlapping cells, each associated with a respective antenna and base station.

15 Each cell contains a base station for radio communication with all of the mobile radios in that cell. Base stations are interconnected by other means of communication, usually fixed land-lines arranged in a grid or meshed structure, allowing mobile radios throughout the cell coverage area to communicate with each other as well as with the public telephone network outside the cellular mobile radio network.

Cellular mobile radio networks which use phased array antennas are known: such an antenna comprises an array (usually eight or more) individual antenna elements such as dipoles or patches. The antenna has a radiation pattern which is a main lobe and sidelobes. The centre of the main lobe is the antenna's direction of maximum sensitivity in reception mode and the direction of its main output radiation beam in transmission mode. It is a well known property of a phased array antenna that if signals received by antenna elements are delayed by a delay which varies with element distance from an edge of the array, then the antenna main radiation beam is steered towards the direction of increasing delay. The angle between main radiation beam centres corresponding to zero and non-zero variation in delay, i.e. the angle of tilt, depends on the rate of change of delay with distance across the array.

Delay may be implemented equivalently by changing signal phase, hence the expression phased array. The main beam of the antenna pattern can therefore be altered by adjusting the phase relationship between signals fed to antenna elements. This allows the beam to be steered to modify the coverage area of the antenna.

- 5 Operators of phased array antennas in cellular mobile radio networks have a requirement to adjust their antennas' vertical radiation pattern, i.e. the pattern's cross-section in the vertical plane. This is necessary to alter the vertical angle of the antenna's main beam, also known as the "tilt", in order to adjust the coverage area of the antenna. Such adjustment may be required, for example, to compensate for change in cellular
- 10 network structure or number of base stations or antennas. Adjustment of antenna angle of tilt is known both mechanically and electrically, either individually or in combination.

Antenna angle of tilt may be adjusted mechanically by moving antenna elements or their housing (radome): it is referred to as adjusting the angle of "mechanical tilt". As described earlier, antenna angle of tilt may be adjusted electrically by changing time

15 delay or phase of signals fed to or received from each antenna array element (or group of elements) without physical movement: this is referred to as adjusting the angle of "electrical tilt".

When used in a cellular mobile radio network, a phased array antenna's vertical radiation pattern (VRP) has a number of significant requirements:

- 20
1. high boresight gain;
  2. a first upper side lobe level sufficiently low to avoid interference to mobiles using a base station in a different network;
  3. a first lower side lobe level sufficiently high to allow communications in the immediate vicinity of the antenna.

25 The requirements are mutually conflicting, for example, increasing the boresight gain will increase the level of the side lobes. A first upper side lobe level, relative to the boresight level, of -18dB has been found to provide a convenient compromise in overall system performance.

30 The effect of adjusting either the angle of mechanical tilt or the angle of electrical tilt is to reposition the boresight so that, for an array lying in a vertical plane, it points either above or below the horizontal plane, and hence changes the coverage area of the

antenna. It is desirable to be able to vary both the mechanical tilt and the electrical tilt of a cellular radio base station's antenna: this allows maximum flexibility in optimisation of cell coverage, since these forms of tilt have different effects on antenna ground coverage and also on other antennas in the station's immediate vicinity. Also, operational efficiency is improved if the angle of electrical tilt can be adjusted remotely from the antenna assembly. Whereas an antenna's angle of mechanical tilt may be adjusted by re-positioning its radome, changing its angle of electrical tilt requires additional electronic circuitry which increases antenna cost and complexity. Furthermore, if a single antenna is shared between a number of operators it is preferable to provide a different angle of electrical tilt for each operator.

The need for an individual angle of electrical tilt from a shared antenna has hitherto resulted in compromises in the performance of the antenna. The boresight gain will decrease in proportion to the cosine of the angle of tilt due to a reduction in the effective aperture of the antenna (this is unavoidable and happens in all antenna designs). Further reductions in boresight gain may result as a consequence of the method used to change the angle of tilt.

R. C. Johnson, Antenna Engineers Handbook, 3rd Ed 1993, McGraw Hill, ISBN 0 - 07 - 032381 - X, Ch 20, Figure 20-2 discloses a known method for locally or remotely adjusting a phased array antenna's angle of electrical tilt. In this method a radio frequency (RF) transmitter carrier signal is fed to the antenna and distributed to the antenna's radiating elements. Each antenna element has a respective phase shifter associated with it so that signal phase can be adjusted as a function of distance across the antenna to vary the antenna's angle of electrical tilt. The distribution of power to antenna elements when the antenna is not tilted is proportioned so as to set the side lobe level and boresight gain. Optimum control of the angle of tilt is obtained when the phase front is controlled for all angles of tilt so that the side lobe level is not increased over the tilt range. The angle of electrical tilt can be adjusted remotely, if required, by using a servo-mechanism to control the phase shifters.

This prior art method antenna has a number of disadvantages. A phase shifter is required for every antenna element. The cost of the antenna is high due to the number of phase shifters required. Cost reduction by applying delay devices to groups of antenna elements instead of individual elements increases the side lobe level. Mechanical coupling of delay devices is used to adjust delays, but it is difficult to do this correctly;

moreover, mechanical links and gears are required resulting in a non-optimum distribution of delays. The upper side lobe level increases when the antenna is tilted downwards thus causing a potential source of interference to mobiles using other base stations. If the antenna is shared by a number of operators, the operators have a  
5 common angle of electrical tilt instead of different angles. Finally, if the antenna is used in a communications system having (as is common) up-link and down-link at different frequencies (frequency division duplex system), the angle of electrical tilt in transmit is different to that in receive.

International Patent Application Nos. PCT/GB2002/004166 and PCT/GB2002/004930  
10 describe locally or remotely adjusting an antenna's angle of electrical tilt by means of a difference in phase between a pair of signal feeds connected to the antenna.

It is an object of the present invention to provide an alternative form of phased array antenna system.

- 15 The present invention provides a phased array antenna system with variable electrical tilt and comprising an array of antenna elements characterised in that it incorporates:
- a) a divider for dividing a radio frequency (RF) carrier signal into first and second signals,
  - b) a variable phase shifter for introducing a variable relative phase shift between the  
20 first and second signals,
  - c) a phase to power converter for converting the relatively phase shifted first and second signals into signals whose powers are a function of the relative phase shift,
  - d) first and second power splitters for dividing the converted signals into at least two sets of divided signals, the total number of divided signals in the sets being at least  
25 equal to the number of antenna elements in the array,
  - e) power to phase converters for combining pairs of divided signals from different power splitters to provide vector sum and difference components with appropriate phase for supply to respective pairs of antenna elements located at like distances with respect to an array centre.

30 In its various embodiments the invention can be configured to provide a variety of advantages, that is to say it:

- a) requires only one phase shifter or time delay device per operator to set the angle of electrical tilt.



- b) can provide a good level of side lobe suppression.
- c) has a controlled upper side lobe level when tilted downwards.
- d) can provide different angles of tilt for different operators when used as a shared antenna.
- 5 e) can provide either local, or remote, control of the angle of electrical tilt.
- f) can be implemented with lower cost than contemporary antennas having a similar level of performance.
- g) can have an angle of electrical tilt at transmit frequencies that is either the same as or different to the angle of electrical tilt at receive frequencies, at the operator's
- 10 option:

The system of the invention may have an odd number of antenna elements comprising a central antenna element between each pair of antenna elements. It may include a third power splitter connected between the phase to power converter and one of the first and second power splitters and arranged to divert to the central element a proportion of the

15 power from the phase to power converter.

The phase to power and power to phase converters may be combinations of phase shifters and quadrature hybrid couplers. The divider, phase shifter, phase to power and power to phase converters and power splitters may be co-located with the array of antenna elements as an antenna assembly, and the assembly may have a single RF

20 input power feed from a remote source.

The divider and phase shifter may be located remotely from the phase to power and power to phase converters, the power splitters and the array of antenna elements which are co-located as an antenna assembly, and the assembly may have dual RF input power feeds from a remote source. They may be co-located with the remote source for

25 use by an operator in varying angle of electrical tilt.

The system may include duplexers to combine signals passing from or divided signals passing to different operators which share the antenna system. The power splitters may be arranged to provide for the antenna elements to receive drive voltages which fall from a maximum centrally of the antenna array to a minimum at array ends.

30 One power splitter may be arranged to provide a set of voltages which rise from a minimum to a maximum associated with the antenna array centre and its ends

respectively, as appropriate to establish a progressive phase front across the antenna array, the phase front being substantially linear as a angle of tilt is increased in a working range of tilt, as required for reasonable boresight gain and side lobe suppression.

In an alternative aspect, the present invention provides a method of providing variable electrical tilt in a phased array antenna system comprising an array of antenna elements characterised in that the method incorporates the steps of:

- a) dividing a radio frequency (RF) carrier signal into first and second signals,
- b) introducing a variable relative phase shift between the first and second signals,
- c) converting the relatively phase shifted first and second signals into signals whose powers are a function of the relative phase shift,
- d) dividing the converted signals into at least two sets of divided signals, the total number of divided signals in the sets being at least equal to the number of antenna elements in the array,
- e) combining pairs of divided signals from different power splitters to provide vector sum and difference components with appropriate phase and supplying the components to respective pairs of antenna elements located at like distances with respect to an array centre.

The method may include providing for a central antenna element of the array to receive power diverted to it from the phase to power converter. It may include feeding power from a remote source to a single RF input of an assembly comprising the divider, phase shifter, phase to power and power to phase converters and power splitters co-located together.

The divider and phase shifter may be co-located with a remote source and the method may include feeding power from the source via dual RF feeds to inputs of an assembly comprising the phase to power and power to phase converters and power splitters co-located together. The method may include the step of an operator using the divider and phase shifter in varying angle of electrical tilt.

The method may include combining signals passing from or dividing signals passing to different operators which share the antenna system. It may include providing for the antenna elements to receive drive voltages which fall from a maximum centrally of the antenna array to a minimum at array ends. It may include providing for one power splitter to output a set of voltages which rise from a minimum to a maximum associated with the

antenna array centre and its ends respectively, as appropriate to establish a progressive phase front across the antenna array, the phase front being substantially linear as an angle of tilt is increased in a working range of tilt, as required for reasonable boresight gain and side lobe suppression.

- 5 In order that the invention might be more fully understood, embodiments thereof will now be described, by way of example only, with reference to the accompanying drawings, in which:-

Figure 1 shows a phased array antenna's vertical radiation pattern (VRP) with zero and non-zero angles of electrical tilt;

- 10 Figure 2 illustrates a prior art phased array antenna having an adjustable angle of electrical tilt;

Figure 3 is a block diagram of a phased array antenna system of the invention in a single feeder application;

- 15 Figure 4 shows relationships between voltage outputs and input phase difference in a phase to power converter used in the Figure 3 system;

Figure 5 is equivalent to Figure 4 with power substituted for voltage;

Figure 6 gives examples of possible voltage distributions at outputs of a voltage splitter used in the Figure 3 system;

- 20 Figure 7 is a block diagram of a part of a further phased array antenna system of the invention, and illustrates phase shifting, phase to power conversion and power division;

Figure 8 is a block diagram of the remainder of the phased array antenna system of Figure 7, and shows power to phase conversion, phase shifting and antenna elements; schematically

- 25 Figure 9 illustrates location, spacing and drive signal phase of antenna elements in the Figure 7 system;

Figure 10 is a block diagram of part of a still further phased array antenna system of the invention, and illustrates a dual feeder implementation using phase shifting,

phase to power conversion and power division with generation of an additional signal for a central antenna element;

Figure 11 illustrates the remainder of the phased array antenna system of Figure 10, and shows an antenna array with a single central antenna element (element spacing is not to scale);

Figure 12 illustrates use of the invention with a single feeder;

Figure 13 shows a modification to the invention allowing angle of electrical tilt in transmit mode to be different to that in receive mode; and

Figure 14 is a block diagram of another phased array antenna system of the invention illustrating antenna sharing by multiple users with dual feeds and joint transmit/receive capability.

Referring to Figure 1, there are shown vertical radiation patterns (VRP) 10a and 10b of an antenna 12 which is a phased array of individual antenna elements (not shown). The antenna 12 is planar, has a centre 14 and extends perpendicular to the plane of the drawing. The VRPs 10a and 10b correspond respectively to zero and non-zero variation in delay or phase of antenna element signals with array element distance across the antenna 12 from an array edge. They have respective main lobes 16a, 16b with centre lines or "boresights" 18a, 18b, first upper sidelobes 20a, 20b and first lower sidelobes 22a, 22b; 18c indicates the boresight direction for zero variation in delay for comparison with the non-zero equivalent 18b. When referred to without the suffix a or b, e.g. sidelobe 20, either of the relevant pair of elements is being referred to without distinction. The VRP 10b is tilted (downwards as illustrated) relative to VRP 10a, i.e. there is an angle - the angle of tilt - between main beam centre lines 18b and 18c which has a magnitude dependent on the rate at which delay varies with distance across the antenna 12.

The VRP has to satisfy a number of criteria: a) high boresight gain; b) the first upper side lobe 20 should be at a level low enough to avoid causing interference to mobiles using another base station; and c) the first lower side lobe 22 should be at a level sufficient for communications to be possible in the antenna 12's immediately vicinity. These requirements are mutually conflicting, for example, maximising boresight gain increases side lobes 20, 22. Relative to a boresight level (length of main beam 16), a first upper side lobe level of -18dB has been found to provide a convenient compromise in overall

system performance. Boresight gain decreases in proportion to the cosine of the angle of tilt due to reduction in the antenna's effective aperture. Further reductions in boresight gain may result depending on how the angle of tilt is changed.

5 The effect of adjusting either the angle of mechanical tilt or the angle of electrical tilt is to reposition the boresight so that it points either above or below the horizontal plane, and hence adjust the coverage area of the antenna. For maximum flexibility of use, a cellular radio base station preferably has available both mechanical tilt and electrical tilt since each has a different effect on ground coverage and also on other antennas in the immediate vicinity. It is also convenient if an antenna's electrical tilt can be adjusted  
10 remotely from the antenna. Furthermore, if a single antenna is shared between a number of operators, it is preferable to provide a different angle of electrical tilt for each operator, although this compromises antenna performance in the prior art.

Referring now to Figure 2, a prior art phased array antenna system 30 is shown in which the angle of electrical tilt is adjustable. The system 30 incorporates an input 32 for a  
15 radio frequency (RF) transmitter carrier signal, the input being connected to a power distribution network 34. The network 34 is connected via phase shifters  $\Phi_{i.E0}$ ,  $\Phi_{i.E1L}$  to  $\Phi_{i.E[n]L}$  and  $\Phi_{i.E1U}$  to  $\Phi_{i.E[n]U}$  to respective radiating antenna elements  $E0$ ,  $E1L$  to  $E[n]L$  and  $E1U$  to  $E[n]U$  respectively of the phased array antenna system 30: here suffixes U and L indicate upper and lower respectively, n is an arbitrary positive integer  
20 greater than unity which defines phased array size, and dotted lines such as 36 indicating the relevant element may be replicated or removed as required for any desired array size.

The phased array antenna system 30 operates as follows. An RF transmitter carrier signal is fed to the power distribution network 34 via the input 32: the network 34 divides  
25 this signal (not necessarily equally) between the phase shifters  $\Phi_{i.E0}$ ,  $\Phi_{i.E1L}$  to  $\Phi_{i.E[n]L}$  and  $\Phi_{i.E1U}$  to  $\Phi_{i.E[n]U}$ , which phase shift their respective divided signals and pass them on with phase shifts to associated antenna elements  $E0$ ,  $E1L$  to  $E[n]L$ ,  $E1U$  to  $E[n]U$  respectively. The phase shifts are chosen to select an appropriate angle of electrical tilt. The distribution of power between the antenna elements  $E0$  etc. when the  
30 angle of tilt is zero is chosen to set the side lobe level and boresight gain appropriately. Optimum control of the angle of electrical tilt is obtained when the phase front across the array of elements  $E0$  etc. is controlled for all angles of tilt so that the side lobe level is not increased significantly over the tilt range. The angle of electrical tilt can be adjusted

remotely, if required, by using a servo-mechanism to control the phase shifters  $\Phi_{iE0}$ ,  $\Phi_{iE1L}$  to  $\Phi_{iE[n]L}$  and  $\Phi_{iE1U}$  to  $\Phi_{iE[n]U}$ , which may be mechanically actuated.

The phased array antenna system 30 has a number of disadvantages as follows:

- 5 a) a phase shifter is required for each antenna element, or (less advantageously) per group of elements;
- b) the cost of the antenna is high due to the number of phase shifters required;
- c) cost reduction by applying phase shifters to respective groups of elements instead of individual antenna elements increases the side lobe level;
- 10 d) mechanical coupling of phase shifters to set delays correctly is difficult and mechanical links and gears are used which result in a non-optimum delay scheme;
- e) the upper side lobe level increases when the antenna is tilted downwards causing a potential source of interference to mobiles using other base stations;
- f) if an antenna is shared by different operators, all must use the same angle of electrical tilt;
- 15 g) in a system with up-link and down-link at different frequencies (frequency division duplex system), the angle of electrical tilt in transmit is different from that in receive;

Referring now to Figure 3, a phased array antenna system 40 of the invention is shown which has an adjustable angle of electrical tilt. The system 40 incorporates an input 42 for an RF transmitter carrier signal: the input 42 is connected as input to a power splitter 44 providing two output signals  $V_{1a}$ ,  $V_{1b}$  which are input signals to a variable phase shifter 46 and a fixed phase shifter 48 respectively. The phase shifters 46 and 48 may equivalently be considered as time delays. They provide respective output signals  $V_{2a}$  and  $V_{2b}$  to a phase to power converter 50, which in turn provides output signals  $V_{3a}$  and  $V_{3b}$  to two power splitters 52 and 54 respectively. The phase to power converter 50 will be described in more detail later. The power splitters 52 and 54 have  $n$  outputs such as 52a and 54a respectively: here  $n$  is a positive integer equal to 2 or more, and dotted arrow outputs 52b and 54b indicate the output in each case may be replicated as required for any desired phased array size.

30 The power splitter outputs such as 52a and 54a provide output signals  $V_{a1}$  to  $V_{a[n]}$  and  $V_{b1}$  to  $V_{b[n]}$  respectively which are grouped in pairs  $V_{ai}/V_{bi}$  ( $i = 1$  to  $n$ ), one signal from each splitter in each pair; each pair of signals  $V_{ai}/V_{bi}$  is connected (not shown) to a

respective power to phase converter 56<sub>i</sub>. A first power to phase converter 56<sub>1</sub> receives inputs Va1/Vb1 and provides drive signals via respective fixed phase shifters 58U1 and 58L1 to a first pair of equispaced phased array antenna elements 60U1 and 60L1 which are the innermost elements of an array 60. Pairs of adjacent antenna elements such as 60U1 and 60L1 are spaced apart by a centre spacing 62. A second power to phase converter 56<sub>2</sub> receives input signals Va2 and Vb2: it provides drive signals via respective fixed phase shifters 58U2 and 58L2 to a second pair of phased array antenna elements 60U2 and 60L2, which are next to respective innermost elements 60U1 and 60L1. Likewise, an nth power to phase converter 56<sub>n</sub> receives inputs Va[n]/Vb[n]: it provides drive signals via respective fixed phase shifters 58Un and 58Ln to an nth pair of phased array antenna elements 60n and 60Ln. This nth pair have centres 64 distant (n - 1) centre spacings 62 from respective innermost elements 60U1 and 60L1. Here as before n is an arbitrary positive integer equal to or greater than 2 but equal to the value of n for the power splitters 52 and 54, and phased array size is 2n antenna elements. The power to phase converter 56<sub>n</sub> and outermost antenna elements 60Un and 60Ln are shown dotted to indicate they may be replicated as required for any desired phased array size.

The phased array antenna system 40 operates as follows. An RF transmitter carrier signal is fed (single feeder) via the input 42 to the power splitter 44 where it is divided into signals V1a and V1b of equal power. The signals V1a and V1b are fed to the variable and fixed phase shifters 46 and 48 respectively. The variable phase shifter 46 applies a operator-selectable phase shift or time delay, and the degree of phase shift applied here controls the angle of electrical tilt of the phased array of antenna elements 58U1 etc. The fixed phase shifter 48 applies a fixed phase shift which for convenience is arranged to be half the maximum phase shift  $\phi_M$  applicable by the variable phase shifter 46. This allows V1a to be variable in phase in the range  $-\phi_M/2$  to  $+\phi_M/2$  relative to V1b, and these signals after phase shift become V2a and V2b as has been said after output from the phase shifters 46 and 48.

The phase to power converter 50 combines its input signals V2a and V2b and generates from them two output signals V3a and V3b having powers relative to one another which depend on the relative phase difference between its inputs. The power splitters 52 and 54 divide signals V3a and V3b into n output signals Va1 to Va[n] and Vb1 to Vb[n] respectively, where the power of each signal in each set Va1 etc or Vb1 etc is not

necessarily equal to the powers of the other signals in its set. Splitter 52 is an 'amplitude taper splitter' controlling element power and splitter 54 is a 'tilt splitter' controlling tilt.

The variation of signal powers across the sets  $Va_1$  etc and  $Vb_1$  etc is different for different numbers of antenna elements 60U1 etc in the array 60, and examples will be described later for arrays of fixed sizes.

The output signals  $Va_1/Vb_1$  to  $Va[n]/Vb[n]$  are grouped in pairs from different splitters but with like-numbered suffixes, i.e. pairs  $Va_1/Vb_1$ ,  $Va_2/Vb_2$  etc. The pairs  $Va_1/Vb_1$  etc. are fed to respective power to phase converters 56<sub>1</sub> etc., which convert each pair into two antenna element drive signals with a relative phase difference between them. Each drive signal passes via a respective fixed phase shifter 58U1 etc. to a respective antenna element 60U1 etc. The fixed phase shifters 58U1 etc. impose fixed phase shifts which between different antenna elements 60U1 etc. vary linearly according to element geometrical position across the array 60: this is to set a zero reference direction (18a or 18b in Figure 1) for the array 60 boresight when the phase difference between the signals  $V1a$  and  $V1b$  imposed by the variable phase shifter 46 is zero. The fixed phase shifters 58U1 etc. are not essential, but they are preferred because they can be used to a) proportion correctly the phase shift introduced by the tilt process, b) optimise suppression of the side lobes over the tilt range, and c) introduce an optional fixed angle of electrical tilt.

It can be shown (as described later) that the angle of electrical tilt of the array 60 is at variable simply by using one variable phase shifter, the variable phase shifter 46. This compares with the prior art requirement to have multiple variable phase shifters, one for every antenna element. When the phase difference introduced by the variable phase shifter 46 is positive the antenna tilts in one direction, and when that phase difference is negative the antenna tilts in the opposite direction.

If there are a number of users, each user may have a respective phased array antenna system 40. Alternatively, if it is required that the users employ a common antenna 60, then each user has a respective set of elements 42 to 58U/58L in Figure 3, and a combining network is required to combine signals from the resulting plurality of sets of phase shifters 58U etc. for feeding to the antenna array 60. Published International Patent Application No. WO 02/082581 A2 describes such a network.



Referring now to Figure 4, this drawing shows the voltages of the phase to power converter output signals V3a and V3b plotted as a function of difference in phase between V2a and V2b introduced by the phase shifter 46. Here V3a and V3b are normalised to a maximum of 1 volt. The phase angles of the signals V3a and V3b remain equal and unchanged as the power of one reduces and that of the other increases as a consequence of changing the relative phase difference between V2a and V2b introduced by variable phase shifter 46. However, a negative voltage for V3b represents a 180 degree phase shift of that signal relative to V3a.

Figure 5 is equivalent to Figure 4 except that it is a plot of power, normalised to 1 watt, against phase for signals Va3 and Vb3, their powers being denoted by P3a and P3b respectively. It shows that when the antenna is not tilted, i.e. when phase = 0, P3a is a maximum and P3b = 0: therefore all signal power is fed to the first splitter 52 when phase = 0 and the second splitter 54 receives zero power. Hence, the distribution of voltages (Va1, Va2,...Va[n]), when the antenna is not tilted, determines the boresight gain and the level of the side lobes for zero tilt.

The effects of different voltage distributions across the elements of a phased array antenna are well known. Figure 6 illustrates three different voltage distributions for a phased array antenna having seventeen antenna elements, voltage being plotted against antenna element number: here the antenna elements are considered to be arranged in a vertical plane, a central antenna element being numbered 0. Positive and negative antenna element numbers are assigned according to whether the antenna element in each case is above or below the central antenna element 0, and antenna element number magnitude in each case is proportional to the separation between the relevant element and the central element. Antenna element voltage is normalised by division by the central antenna element voltage, so the central antenna element 0 has voltage 1.0 relative to other antenna elements.

If a phased array antenna is primarily required to have maximum boresight gain then a rectangular distribution of antenna element voltages is used, i.e. the antenna elements all have the same drive voltage as indicated by a linear horizontal plot 70. If maximum suppression of side lobe level is required, a binomial distribution 72 of antenna element voltages is used. Alternatively, a distribution 74 may be used which is part rectangular and part binomial. The distribution 74 is half the sum of the distributions 70 and 72. In

distribution 72, outermost elements 8 and -8 receive zero power and can be omitted from the phased array.

It has been found to be advantageous in this invention for the level of the side lobes to be optimised at the maximum angle of electrical tilt. Side lobe levels will then be less than the level at the maximum angle of tilt for all tilt angles below the maximum. Referring to Figure 3 once more, to tilt the phased array antenna 60 electrically the power fed to the second splitter 54 is increased from zero; the  $i$ th upper and lower antenna elements 60U $i$  and 60L $i$  ( $i = 1$  to  $n$ ) then receive drive signals having phase and amplitude determined by vectorially combining signals  $Va[i]$  and  $Vb[i]$ . The phase  $\phi_u[i]$  of the signal fed to the  $i$ th upper element 60U $[i]$  is given by:

$$\phi_u[i] = \tan^{-1} \left( \frac{Vb[i]}{Va[i]} \right) \quad (1)$$

The phase shift  $\phi_l[i]$  of the signal fed to the  $i$ th lower element 60L $[i]$  is given by:

$$\phi_l[i] = -\tan^{-1} \left( \frac{Vb[i]}{Va[i]} \right) \quad (2)$$

Equations (1) and (2) show that the phase of the drive signal applied to the  $i$ th upper antenna element 60U $[i]$  is in the opposite direction to that applied to the  $i$ th lower antenna element 60L $[i]$ . Now the voltages output from the second splitter 54 are chosen to increase from  $Vb_1$  to  $Vb[n]$ , i.e.  $Vb[n] > \dots Vb[i] > \dots Vb_2 > Vb_1$ ; consequently, from Equations (1) and (2) a progressive phase front is established across the antenna 60 causing it to have a non-zero angle of electrical tilt. Furthermore, the phase front remains substantially linear as the angle of tilt is increased, thus preserving boresight gain and side lobe suppression. It can be seen from Equations (1) and (2) that the tilt sensitivity is determined by the power delivered by the second splitter 54. When implemented in this way the phased array antenna system 40 has a tilt sensitivity that is typically 1 degree of electrical tilt per 10 degrees of shift in phase.

The antenna system 40 may be implemented as a single feeder system or a dual feeder system (per user in each case). In a single feeder system, a single signal feed 42 supplies a signal  $V_{in}$  to the antenna array 60 which may be mounted on a mast, and

items 44 to 64 in Figure 3 are mounted with the antenna array. This has the advantage that only one signal feed is needed to pass to the antenna system from a remote user, but against that a remote user cannot adjust the angle of electrical tilt without access to the antenna system. Also, operators sharing a single antenna would all have the same  
5 angle of electrical tilt.

In a dual feeder system, two signals V2a and V2b are fed to an antenna array: items 42 to 48 (tilt control components) in Figure 3 may be located with a user remotely from the antenna array 60, and items 50 to 64 are located with the antenna array. The user may now have direct access to the phase shifter 46 to adjust the angle of electrical tilt. It is  
10 also convenient to reduce tilt sensitivity to reduce the effects of phase differences between feeders and hence a difference between the angle of electrical tilt required by the operator and that at the antenna. With a respective set of tilt control components 42 to 48 located with each user, and at the input side of a frequency selective combiner located at an operator's base station, it is possible to implement a shared antenna  
15 system with an individual angle of tilt for each operator.

To reduce the effects of variations in amplitude and phase between two feeders in a dual feeder system of the invention, tilt sensitivity may be decreased by reducing the power from the second splitter 54 used for electrical tilting. Tilting power from the second splitter 54 can be reduced by (a) feeding some of the power from splitter 54 to an  
20 additional antenna element whose phase shift is constant and positioned in the centre of the antenna array, or by (b) diverting some of this power into a termination, or (c) a combination of (a) and (b).

In order to avoid an undue reduction in the maximum value of antenna boresight gain it is preferable to divert some of the second splitter power into an additional central antenna  
25 element. When one half of the total second splitter power is fed to a central antenna element the tilt sensitivity is typically 20 degrees of phase shift per 1 degree of electrical tilt. As the tilt passes through zero the phase shift on the central antenna element changes by 180 degrees. This has the effect of introducing asymmetry between the levels of the upper and lower side lobes, unlike Figure 1 where these lobes are  
30 symmetrical. In particular, this asymmetry suppresses the upper side lobe (corresponding to 20a) to further reduce the possibility of interference to mobile telephones using other base stations.

The embodiment 40 of the invention provides a number of advantages:

1. tilt is implemented with a single variable time delay device or phase shifter per user instead of per antenna element;
2. phase and amplitude tapers (**## explain**) remain substantially constant over a range of tilt (**## state range of tilt**); ( 4 degrees to 6 degrees, depending on frequency); here 'taper' is amplitude or phase profile across antenna elements.
3. side lobe suppression remains effective throughout the tilt range and can be controlled to less than 18dB below the boresight level;
4. tilt sensitivity can be set to an optimum;
5. individual tilt angles are available for sharing of an antenna by multiple users;
6. the angle of tilt in transmit mode can be either the same as or different to from the angle of tilt in receive mode despite these modes having different frequencies, as will be described later;
7. asymmetrical side lobe levels are obtainable to reduce the potential for interference with mobiles using other base stations.

Referring now to Figure 7, there is shown a circuit 80 for phase to power conversion and voltage splitting similar to the upper portion of Figure 3. Only points of difference will be described. The differences as compared to Figure 3 are that a fixed phase shifter 82 is connected series (instead of in parallel) with a variable phase shifter 84, an example of a phase to power conversion is given, and two splitters 88a and 88b each divide into seven outputs Va1/Vb1 etc.. Signals pass from the fixed and variable phase shifters 82 and 84 to a quadrature hybrid directional coupler 86 having four terminals A, B, C and D. input-output paths between pairs of terminals A to D are indicated by curved lines such as 92. (Arthur - I can't find #90 or #92 in the figures: I didn't use 90 to avoid confusion with phase shift, and I've now put in 92) Phase to power conversion is obtained from the combination of the fixed phase shifter 82 and coupler 86. As indicated by markings -90 and -180, the coupler 86 phase shifts its input signals by -90 or -180 depending upon where such signals are input and output: signal V2a from fixed phase shifter 86 is input to terminal B and output at terminals A and C to splitters 88a and 88b with phase shifts -90 degrees and -180 degrees respectively. Similarly, signal V2b from variable phase shifter 84 is input to terminal D and output at terminals A and C to splitters 88a and 88b

180 degrees and -90 degrees respectively. The splitters 88a and 88b provide power division broadly speaking as described earlier.

Referring now also to Figure 8, a phased array 94 is connected (not shown) to the circuit 80 and comprises fourteen antenna elements 96E1U to 96E7U and 96E1L to 96E7L shown in upper/lower pairs such as 96E1U and 96E1L. Figure 8 shows the electrical connection scheme in an illustrationally convenient manner with pairs of elements back to back, but in practice the antenna elements 96E1U *etc.* are arranged in a straight line and all point in the same direction. The upper antenna elements 96E1U to 96E7U are connected via respective preset phase shifters 98U1 to 98U7 and fixed -90 degree phase shifters 99U1 to 99U7 to quadrature hybrid directional couplers 100C1 to 100C7. The lower antenna elements 96E1L to 96E7L are connected via respective preset phase shifters 98L1 to 98L7 to the couplers 100C1 to 100C7 also, there being a respective coupler 100Ci for each upper/lower element pair 96EUi/96ELi ( $i = 1, 2, \dots, 7$ ). The preset phase shifters 98L1 to 98L7 are optional: they give the antenna array 96 a prearranged boresight direction corresponding to zero electrical tilt and optimise suppression of side lobes over the tilt range.

Each coupler 100C1 *etc.* receives a respective pair of input signals from the splitters 88a and 88b, i.e. the  $i$ th coupler 100Ci receives input signals  $V_{ai}$  and  $V_{bi}$  with  $i$  having values 1 to 7 as before. Each coupler 100C1 *etc.* is equivalent to the coupler 86 mentioned earlier, i.e. each has four terminals A to D with intervening input-output paths indicated by curved lines such as 102. Coupler 100C1 receives input of  $V_{a1}$  and  $V_{b2}$  at B and D respectively and generates -90 degree and -180 degree phase shifted versions of each: output A receives  $V_{a1}$  phase shifted -90 degrees and  $V_{b2}$  phase shifted -180 degrees, and output C receives  $V_{a1}$  phase shifted -180 degrees and  $V_{b2}$  phase shifted -90 degrees. Output A is connected via -90 degree phase shifter 99U1 and preset phase shifter 98U1 to antenna element 96E1U, and output C is connected via preset phase shifter 98L1 to antenna element 96E1L. Similar arrangements apply to power feeds to other upper/lower antenna element pairs 96E2U/96EL2 to 96E7U/96E7L. The  $i$ th quadrature hybrid coupler 100Ci and the -90 degree phase shifter 99Ui in combination provide power-to-phase conversion shown at 56 in Figure 3.

Referring now also to Figure 9, the phased array 96 is shown in its actual linear form, with each antenna element 96E1U *etc.* shown on the left hand side together with a respective vector diagram 110U1 to 110L7 to its right. Vector diagram 110U1 has a resultant arrow 112 arising from the vector addition of vectors  $a_1$  and  $b_1$ , and representing the sum of the signals  $V_{a1}$  and  $V_{b1}$  applied to antenna element 96E1U after various phase shifts as previously described. Similar remarks apply to other antenna elements. The  $i$ th upper antenna element 96EiU receives the vector sum  $a_i + b_i$ , and the  $i$ th lower antenna element 96EiL receives the vector difference  $a_i - b_i$ ,

The voltage and power ratios for the first splitter 88a in Figure 7 are shown in Table 1 below. For convenience of representation the power levels are normalised so that the total power exiting from the splitter 88a is 1 watt. Voltages are square roots of powers so they are relative values also. The antenna element voltage levels have a raised cosine squared distribution. It is similar to curve 74 in Figure 6, except strictly speaking curve 74 is binomial not cosine and curvatures differ.

Table 1

Splitter 88a Output	Voltage Ratio	Power Ratio	
		Power	Decibels
Va7	0.0010	0.000001	-60.0
Va6	0.0825	0.0068	-21.7
Va5	0.2014	0.0406	-13.9
Va4	0.3306	0.1093	-9.6
Va3	0.4494	0.2020	-7.0
Va2	0.5404	0.2920	-5.4
Va1	0.5911	0.3493	-4.6

The voltage and power ratios for the second splitter 88b in Figure 7 are shown in Table 2, expressed as relative values in the same way as those of Table 1.

Table 2

Splitter 88b Output	Voltage Ratio	Power Ratio	
		Power	Decibels
Vb7	0.2607	0.0680	-11.7
Vb6	0.4346	0.1889	-7.2
Vb5	0.5032	0.2532	-6.0
Vb4	0.4910	0.2411	-6.2
Vb3	0.4086	0.1670	-7.8
Vb2	0.2702	0.0730	-11.4
Vb1	0.0946	0.0090	-20.5

Referring now to Figures 10 and 11, there is shown a modification to the embodiment described with reference to Figures 7 to 9, and parts described earlier are like referenced. It is particularly suitable for a dual feeder implementation of the invention where it is preferable to reduce tilt sensitivity to reduce possible tilt error due to the effect of phase differences between signal feeders. There are two modifications: the first modification is to insert an extra splitter 120 - a two way splitter - between output C of coupler 86 and the second splitter 88b. This allows some of the power hitherto fed to the second splitter 88b to be diverted to provide another signal Vb0. As shown in Figure 11, the array 94 is modified by the introduction of an additional antenna element 122, which receives the Vb0 signal via a fixed 180 degree phase shifter 124. The additional antenna element 122 is located centrally of the array 94, which is otherwise unchanged; i.e. the element 122 is positioned a distance  $S/2$  from each of antenna elements 96E1U and 96E1L, where  $S$  is the spacing between any other adjacent pair of antenna elements such as 96E1U and 96E2U. It is noted that for illustrational convenience the spacing between additional antenna element 122 is shown as equal to other spacings  $S$  but is labelled  $S/2$ .

Figure 11 is equivalent to Figure 9 with the addition of antenna element 122 and phase shifter 124: as indicated by vector diagram 126, this element 122 receives the signal Vb0 without subtraction of any vector signal from splitter 88a. The voltage and power ratios for splitter 88b are shown in Table 3 below. As before the power levels are normalised so that the total power exiting from splitter 88b is 1 watt. Equivalents for splitter 88a are as in Table 1 above.

Table 3

Splitter Output	Voltage Ratio	Power Ratio	
		Power	Decibels
Vb7	0.2355	0.0555	-12.6
Vb6	0.3925	0.1540	-8.1
Vb5	0.4544	0.2065	-6.9
Vb4	0.4434	0.1966	-7.1
Vb3	0.3690	0.1362	-8.7
Vb2	0.2440	0.0595	-12.3
Vb1	0.0855	0.0073	-21.4
Vb0	0.4294	0.1844	-7.3

The direction of maximum gain of a phased array antenna is determined by the phase and amplitude of the voltages on its antenna elements. If the performance of the antenna is required to remain broadly the same over a band of frequencies then the phase and amplitude of the signals fed to the elements should remain the same as the frequency is changed. A length of transmission line has a delay which is constant and independent of frequency, and hence the phase shift it introduces in a signal passing along it increases with frequency. Consequently a phased array antenna which uses transmission lines as delay elements will have a performance that changes with frequency. A broadband



directional coupler has the property that the phase relationships at its terminals remain constant over its working range of frequencies. Hence if directional couplers are used as delay elements in a phased array antenna, the antenna's performance will remain constant with frequency. It may also be advantageous, as a means of compensating for changes in side lobe level with the angle of electrical tilt, to retain the use of transmission lines as a delay element. Maximum design flexibility results if a combination of a transmission line and a directional coupler is used for delay/phase shift purposes.

Referring now to Figure 12, part of Figure 3 has been reproduced and modified to illustrate single feed arrangements. Parts previously described are like-referenced with a prefix 100 and only changes will be described. A single signal feed 165 supplies an RF carrier signal to the splitter 142, which together with all components 144 to 160 inclusive are co-located. This requires adjustment of tilt at the antenna array 160, which may be on a mast.

Figure 13 shows a phased array antenna system 171 of the invention equivalent to that shown in Figure 12 with modification for use in both receive and transmit modes. Parts previously described are like-referenced and only changes will be described. The variable phase shifter 146 with which tilt is controlled is now used in transmit (Tx) mode only, and is connected in a transmit path 173 between and in series with bandpass filters (BPF) 175 and 177. There is also a similar receive (Rx) path 179 with a variable phase shifter 181 between and in series with bandpass filters 183 and 185. Transmit and receive frequencies are normally sufficiently different to allow them to be isolated from one another by bandpass filters 175 *etc.* All elements 144 to 160 operate in reverse in receive mode with e.g. splitters becoming recombiners. The only difference between the two modes is that in transmit mode feeder 165 provides input and transmit path 173 is traversed by a transmit signal from left to right, whereas in receive mode receive path 179 is traversed by a receive signal from right to left and feeder 165 provides output. This arrangement is advantageous because it allows the angles of electrical tilt in both transmit and receive modes to be independently adjustable and to be made equal: normally (and disadvantageously) this is not possible because components have frequency dependent properties which differ between the transmit and receive frequencies.

Referring now to Figure 14, a phased array antenna system 200 of the invention is shown for use in transmit and receive modes by multiple (two) operators 201 and 202 of

a single phased array antenna 205. Parts equivalent to those previously described are like referenced with a prefix 200. The drawing has a number of different channels: parts in different channels which are equivalent are numerically like-referenced with one or more suffixes: a suffix T or R indicates transmit or receive channel, a suffix 1 or 2 indicates first or second operator 201 or 202, and a suffix A or B indicates A or B path.

Initially a transmit channel 207T1 of the first operator 201 will be described. This transmit channel has an RF input 242 feeding a splitter 244T1, which divides the input between variable and fixed phase shifters 246T1A and 248T1B. Signals pass from the phase shifters 246T1A and 248T1B to bandpass filters (BPF) 209T1A and 209T1B in different duplexers 211A and 211B respectively. The bandpass filters 209T1A and 209T1B have pass band centres at a frequency of transmission of the first operator 201, this frequency being designated Ftx1 as indicated in the drawing. The first operator 201 also has a frequency of reception designated Frx1, and equivalents for the second operator 202 are Ftx2 and Frx2.

The first operator transmit signal at frequency Ftx1 output from the leftmost bandpass filter 209T1A is combined by the first duplexer 211A with a like-derived second operator transmit signal at frequency Ftx2 output from an adjacent bandpass filter 209T2A. These combined signals pass along a feeder 213A to an antenna tilt network 215 of the kind described in earlier examples, and thence to the phased array antenna 205. Similarly, the other first operator transmit signal at frequency Ftx1 output from bandpass filter 209T1B is combined by the second duplexer 211B with a like-derived second operator transmit signal at frequency Ftx2 output from an adjacent bandpass filter 209T2B. These combined signals pass along a second feeder 213B to the phased array antenna 205 via the antenna tilt network 215. Despite using the same phased array antenna 205, the two operators can alter their transmit angles of electrical tilt both independently and remotely from the antenna 205 merely by adjusting variable phase shifters 246T1A and 246T2A respectively..

Analogously, receive signals returning from the antenna 205 via network 215 and feeders 213A and 213B are divided by the duplexers 211A and 211B. These divided signals are then filtered to isolate individual frequencies Frx1 and Frx2 in bandpass filters 209R1A, 209R2A, 209R1B and 209R2B, which provide signals to variable and fixed phase shifters 246R1A, 246R2A, 248R1B and 248R2B respectively. Receive angles of

electrical tilt are then adjustable by the operators 201 and 202 independently by adjusting their respectively variable phase shifters 246R1A and 246R2A.

## Claims

1. A phased array antenna system with variable electrical tilt and comprising an array of antenna elements characterised in that it incorporates:
  - a) a divider for dividing a radio frequency (RF) carrier signal into first and second signals,
  - b) a variable phase shifter for introducing a variable relative phase shift between the first and second signals,
  - c) a phase to power converter for converting the relatively phase shifted first and second signals into signals whose powers are a function of the relative phase shift,
  - d) first and second power splitters for dividing the converted signals into at least two sets of divided signals, the total number of divided signals in the sets being at least equal to the number of antenna elements in the array,
  - e) power to phase converters for combining pairs of divided signals from different power splitters to provide vector sum and difference components with appropriate phase for supply to respective pairs of antenna elements located at like distances with respect to an array centre.
2. A system according to Claim 1 characterised in that it has an odd number of antenna elements comprising a central antenna element between each pair of antenna elements.
3. A system according to Claim 2 characterised in that it includes a third power splitter connected between the phase to power converter and one of the first and second power splitters and arranged to divert to the central element a proportion of the power from the phase to power converter.
4. A system according to Claim 1 characterised in that the phase to power and power to phase converters are combinations of phase shifters and quadrature hybrid couplers.
5. A system according to Claim 1 characterised in that the divider, phase shifter, phase to power and power to phase converters and power splitters are co-located with the array of antenna elements as an antenna assembly, and the assembly has a single RF input power feed from a remote source.

6. A system according to Claim 1 characterised in that the divider and phase shifter are located remotely from the phase to power and power to phase converters, the power splitters and the array of antenna elements which are co-located as an antenna assembly, and the assembly has dual RF input power feeds from a remote source.
7. A system according to Claim 6 characterised in that the divider and phase shifter are co-located with the remote source for use by an operator in varying angle of electrical tilt.
8. A system according to Claim 6 characterised in that it includes duplexers to combine signals passing from or divide signals passing to different operators which share the antenna system.
9. A system according to Claim 1 characterised in that the power splitters are arranged to provide for the antenna elements to receive drive voltages which fall from a maximum centrally of the antenna array to a minimum at array ends.
10. A system according to Claim 1 characterised in that one power splitter is arranged to provide a set of voltages which rise from a minimum to a maximum associated with the antenna array centre and its ends respectively, as appropriate to establish a progressive phase front across the antenna array, the phase front being substantially linear as a angle of tilt is increased in a working range of tilt, as required for reasonable boresight gain and side lobe suppression.
11. A method of providing variable electrical tilt in a phased array antenna system comprising an array of antenna elements characterised in that the method incorporates the steps of:
  - a) dividing a radio frequency (RF) carrier signal into first and second signals,
  - b) introducing a variable relative phase shift between the first and second signals,
  - c) converting the relatively phase shifted first and second signals into signals whose powers are a function of the relative phase shift,
  - d) dividing the converted signals into at least two sets of divided signals, the total number of divided signals in the sets being at least equal to the number of antenna elements in the array,



- e) combining pairs of divided signals from different power splitters to provide vector sum and difference components with appropriate phase and supplying the components to respective pairs of antenna elements located at like distances with respect to an array centre.
12. A method according to Claim 11 characterised in that the antenna array has an odd number of antenna elements comprising a central antenna element between each pair of antenna elements.
  13. A method according to Claim 12 characterised in that it includes a third power splitter connected between the phase to power converter and one of the first and second power splitters and arranged to divert to the central element a proportion of the power from the phase to power converter.
  14. A method according to Claim 11 characterised in that the phase to power and power to phase converters are combinations of phase shifters and quadrature hybrid couplers.
  15. A method according to Claim 11 characterised in that the divider, phase shifter, phase to power and power to phase converters and power splitters are co-located with the array of antenna elements as an antenna assembly, and the assembly has a single RF input power feed from a remote source.
  16. A method according to Claim 11 characterised in that the divider and phase shifter are located remotely from the phase to power and power to phase converters, the power splitters and the array of antenna elements which are co-located as an antenna assembly, and the assembly has dual RF input power feeds from a remote source.
  17. A method according to Claim 16 characterised in that the divider and phase shifter are co-located with the remote source and the method includes the step of an operator using them in varying angle of electrical tilt.
  18. A method according to Claim 16 characterised in that it includes combining signals passing from or dividing signals passing to different operators which share the antenna system.

19. A method according to Claim 11 characterised in that it includes providing for the antenna elements to receive drive voltages which fall from a maximum centrally of the antenna array to a minimum at array ends.
20. A method according to Claim 11 characterised in that it includes providing for one power splitter to output a set of voltages which rise from a minimum to a maximum associated with the antenna array centre and its ends respectively, as appropriate to establish a progressive phase front across the antenna array, the phase front being substantially linear as a angle of tilt is increased in a working range of tilt, as required for reasonable boresight gain and side lobe suppression.

## ABSTRACT

A phased array antenna system with variable electrical tilt comprises an array 60 of antenna elements 60L1 *etc.* incorporating a divider 44 dividing a radio frequency (RF) carrier signal into two signals between which a phase shifter 46 introduces a variable phase shift. A phase to power converter 50 converts the phase shifted signals into signals with powers dependent on the phase shift. Power splitters 52, 54 divide the converted signals into two sets of divided signals with total number equal to the number of antenna elements in the array. Power to phase converters 56, *etc.* combine pairs of divided signals from different power splitters 52, 54: this provides vector sum and difference components with appropriate phase for supply to respective pairs of antenna elements 60U1, 60L1 *etc.* located equidistant from an array centre. Adjustment of the phase shift provided by phase shifter 46 changes the angle of electrical tilt of the antenna array 60



Figure 1




Figure 2 Prior Art




Figure 3




Figure 4





Figure 5



5/11

Figure 6





FIGURE 7

FIGURE 8





FIGURE 9.



8/11





FIGURE 10




Figure 11



10/11

FIGURE 12



171




FIGURE 13

11/11




FIGURE 14



PCT/GB2004/001297



This Page is inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLORED OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REPERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images  
problems checked, please do not report the  
problems to the IFW Image Problem Mailbox**